

The productive and robust high quality laser printer.

i-SENSYS
LBP6750dn

you can



Network-ready 40ppm mono laser printer with flexible paper supply and double-sided printing.

This black and white laser printer integrates seamlessly into any office environment. Robust, quick and featuring duplex capabilities, it's the productive solution for business workgroups.

40 ppm
MONOCHROME
PRINTING

1600-SHEET
MAXIMUM PAPER
SUPPLY

PCL5e/6
OPTIONAL PS

AUTOMATIC
DOUBLE-SIDED
PRINTING

ENERGY EFFICIENT

INTUITIVE CONTROL
PANEL

Key features

- Productive 40 ppm mono laser printer for business workgroups
- Up to 2400 x 600 dpi resolution with Automatic Image Refinement
- Automatic double-sided printing
- First print out time of only 8 seconds
- Quick recovery from sleep mode for added productivity
- Built-in network interface with optional Wi-Fi printing
- PCL5e/6 with optional Postscript Level 3 for seamless IT integration
- Flexible paper support with maximum capacity of 1600 sheets
- Class leading energy efficiency
- Convenient, easy to use All-in-One cartridge
- Intuitive control panel for easy set up and operation

What's in the Box

Main unit, Cartridge 724, power cord, quick setup guide and warranty card - with user software and manual CDs.

Dimensions (WxDxH)

454 x 424 x 342mm

Supported OS

Windows 7(32/64bit)/
Windows Vista(32/64bit)/XP(32/
64bit server 2008(32/64bit)/
server 2008 R2(64bit)/ 2000
server(32/64bit)/ 2000
Mac 10.4.9 - 10.6.x
(Web distribution only)
Linux (Web distribution only)



PRINT



COPY



FAX



SCAN

Canon

Specifications



- 1 5-line LCD display
- 2 100-sheet multi-purpose tray
- 3 500-sheet cassette
- 4 Optional 2x 500-sheet cassettes
- 5 Cartridge 724
(Optional high yield cartridge is available)

PRINTER ENGINE	Print speed 40 ppm mono (A4) Printing method Monochrome laser beam printing Print quality Up to 2400 x 600 dpi with Automatic Image Refinement Print resolution Up to 600 x 600 dpi Warm-up time 14 sec or less First Page Out Time 8 sec Duty cycle Max. 100,000 pages per month Print margins 5mm top, bottom, left and right [envelope : 10mm]
MEDIA HANDLING	Paper input (Standard) 500-sheet cassette 100-sheet multi-purpose tray Paper input (Option) 500-sheet cassette x 2 Paper output 250-sheet face down, 50-sheet face up. Media types Plain paper, Heavy Paper, Transparency, Label, Index card, Envelope Media sizes Cassette (Standard and optional): A4, B5, A5, A6, LGL, LTR, Executive, 16K, 8.5"×13", Custom sizes: Width 105-215.9mm x Length 148-355.6mm Multi-purpose tray: A4, B5, A5, A6, LGL, LTR, Executive, 16K, 8.5"×13", Custom sizes: Width 76.2-215.9mm x Length 127-355.6mm Media weights Cassette (Standard and optional): 60 to 120 g/m ² Multi-purpose tray: 60 to 199 g/m ²
GENERAL FEATURES	Power requirements 220-240V (±10%) 50/60Hz (±2Hz) Power consumption Maximum: Approx 1,270 W or less Active: Approx 630 W Standby: Approx 13 W Sleep modes: Approx 13 W (Sleep Mode 1), Approx 5.6 W (Sleep Mode 2), Approx 2 W (Sleep Mode 3) Typical Electricity Consumption (TEC): 2.0 kWh/Week Noise level Sound power ¹ : Active: 7.3 B or less Standby: Inaudible Sound pressure ¹ : Active: 55 dB(A) or less Standby: Inaudible Dimensions (W x D x H) 454mm x 424mm x 342mm Weight approx.16.7kg Operating environment Temperature +10 to 30°C (50 to 86°F). Humidity 20% to 80% RH [no condensation] Control panel 5 line LCD display 9 LED indicators 10 Operation keys

CONTROLLER	Processor Speed 333 MHz Memory 128 MB expandable up to 384 MB Printer languages UFR II (Ultra Fast Rendering), PCL5e, PCL6, PostScript Level 3 Emulation(optional) ³ Fonts 93 Scalable fonts, 10 Bitmap fonts, 80 PS fonts (option) Interface and connectivity USB 2.0 High-Speed, 10BASE-T/100BASE-TX, IEEE802.11b/g Wireless Print Server (optional) Operating systems compatibility Win 7(32/64bit)/Win Vista(32/64bit)/XP(32/64bit) server 2008(32/64bit) / server 2008 R2(64bit)/ 2003 server(32/64bit)/ 2000 Mac OS10.4.9 - 10.6.x ² /Linux ²
CONSUMABLES	All-in-One cartridges Standard: Cartridge 724 (6,000 pages ⁴) High yield: Cartridge 724H (12,500 pages ⁴)
ACCESSORIES/ OPTIONS	Items PAPER FEEDER PF-45 (500-sheet cassette) ER-64 (64 MB RAM), ER-128 (128 MB RAM), ER-256 (256 MB RAM) PS ROM-A45 (PostScript 3 Emulation ROM module) PS/Barcode ROM-A45 (PostScript 3 Emulation and Barcode ROM module) Wireless Network Interface Board NB-W2 (IEEE802.11b/g Wireless Print Server)
Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final are subject to change without notice. TM and ©: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All specifications subject to change without notice Footnotes 1. Declared noise emission in accordance with ISO 9296 2. Web distribution only 3. PostScript Level 3 Emulation support requires PS ROM A-45 and expansion RAM, minimum ER-64 (64 MB RAM) 4. Based on ISO/IEC 19752	



The productive and robust high quality laser printer.

i-SENSYS
LBP6750dn

you can



Network-ready 40ppm mono laser printer with flexible paper supply and double-sided printing.

Sales Start Date: **October 2010**

The whole range consists of:

i-SENSYS LBP6000, i-SENSYS LBP6200d, i-SENSYS LBP6300dn, i-SENSYS LBP6650dn, i-SENSYS LBP3460, **i-SENSYS LBP6750dn**

Box Dimensions (W x D x H)

496 x 633 x 447mm

Box Weight

21 kg

Packet style

Pallet

Quantity of item

8

MERCURY CODES

PRODUCT

Name	Mercury Code	EAN Code
i-SENSYS LBP6750dn	4096B007AA	8714574553467

OPTIONS

Accessories	Mercury Code	EAN Code
Paper Feeder PF-45	4098B001AA	4960999661285
PS ROM A-45	3927B002AA	4960999662954
PS Barcode ROM A-45	3927B003AA	4960999662961
EXP.RAM ER-64	0646A038AA	4960999356976
EXP.RAM ER-128	0646A039AA	4960999356990
EXP.RAM ER-256	0646A040AA	4960999356983
Wireless Network Interface Board Nb-W2	0642A039AA	4960999573885



PRINT



COPY



FAX



SCAN

Canon